



## Weather PROOF IR CAMERA

**XT2613**



### SPECIFICATION

Model	XT2613
Image Sensor	1/3" Sony Super HAD Color CCD Sensor
Scanning System	2:1 Interlace
	30 Frames (NTSC)    25 Frames (PAL)
Effective Pixels	525 Lines Interlaced (NTSC)    625 Lines Interlaced (PAL)
Resolution	510 (H) x 492 (V) (NTSC)    500 (H) x 582 (V) (PAL)
Minimum Illumination	480 TV Lines
S/N Ratio	0.5 Lux / F 1.2    0 Lux When IR On
Video Output	More Than 48dB (AGC Off)
Gamma Ratio	1.0 Vp-p composite, 75ohm
White Balance	0.45
Back Light Compensation	Auto
Auto Gain Control	Auto
Iris Mode	Auto
Synchronization	AES
Electronic Shutter	Internal
Lens	1/60 to 1/10,000 sec (NTSC)    1/50 to 1/10,000 sec (PAL)
Power Source	f = 6.0mm / F1.2
Power Consumption	DC12V ± 10%
LED / Effective Length	110mA, 320mA When IR on
Weather Resistance	26 Units IR LED / 30M
Operating Temperature	IP 66
Weight / Dimension	- 10°C to + 55°C
	Approx. 320g / Ø 680.0 x 115.0 (H) mm

*Design and specifications are subject to change without prior notice*

**XTVIEW™**