



Weather PROOF Vari-Focal IR CAMERA

XT 5242



SPECIFICATION

Model	XT5242
Image Sensor	1/3" Sony Exviewr HAD Color CCD Sensor
Scanning System	2:1 Interlace 30 Frames (NTSC) 25 Frames (PAL)
Effective Pixels	525 Lines Interlaced (NTSC) 625 Lines Interlaced (PAL)
Resolution	768 (H) x 494 (V) (NTSC) 752 (H) x 582 (V) (PAL)
Minimum Illumination	520 TV Lines
S/N Ratio	0 Lux When IR On
Video Output	More Than 48dB (AGC Off)
Gamma Ratio	VBS 1.0 Vp-p composite, 75ohm
White Balance	0.45
Back Light Compensation	Auto
Auto Gain Control	Auto
Iris Mode	Auto
Synchronization	AES
Electronic Shutter	Internal
Day & Night time delay, Flicker	1/60 to 1/10,000 sec (NTSC) 1/50 to 1/10,000 sec (PAL)
Lens	Dip Switch Control
Power Source	f = 3.8mm~9.5mm / F1.2
Power Consumption	DC12V ± 10%
LED / Effective Length	180mA, 320mA When IR on
Weather Resistance	42 Units IR LED / >30M
Operating Temperature	IP 66
Weight / Dimension	- 10°C to + 55°C
	77mm (Ø) x 128 mm (H)

Design and specifications are subject to change without prior notice

XTVIEW™